

ANDERSON & ASSOCIATES, INC.

Professional Design Services

www.andassoc.com

Virginia - North Carolina - Tennessee

DATE	DESIGNED	DRAWN	CHECKED	REV. #	COMMENT'S	DATE
27 AUG 07	RJM	MSM	TMK	1		
				2		
				3		
				4		
				5		
				6		
				7		
				8		
				9		
				10		
				11		
				12		
				13		
				14		
				15		
				16		
				17		
				18		
				19		
				20		
				21		
				22		
				23		
				24		
				25		
				26		
				27		
				28		
				29		
				30		
				31		
				32		
				33		
				34		
				35		
				36		
				37		
				38		
				39		
				40		
				41		
				42		
				43		
				44		
				45		
				46		
				47		
				48		
				49		
				50		
				51		
				52		
				53		
				54		
				55		
				56		
				57		
				58		
				59		
				60		
				61		
				62		
				63		
				64		
				65		
				66		
				67		
				68		
				69		
				70		
				71		
				72		
				73		
				74		
				75		
				76		
				77		
				78		
				79		
				80		
				81		
				82		
				83		
				84		
				85		
				86		
				87		
				88		
				89		
				90		
				91		
				92		
				93		
				94		
				95		
				96		
				97		
				98		
				99		
				100		

DATE	REV. #	COMMENTS
27 AUG 07		

DATE _____

FIRST & MAIN

PHASE 1


BLACKSBURG, VIRGINIA

SITE DETAILS 1

DOCUMENT NO.
22559 — 310


NET

May, Michael / 8/20/2007 10:15 AM / u:\22\22559\22559eng\design\plans_lsc\22559_sheet_site_details.dwg



PARKING BLOCK
NOT TO SCALE

NOT TO SCALE



FOR ALL SPACES TO BE DESIGNATED AS ACCESSIBLE, THE VIRGINIA STANDARD "RESERVED PARKING" SIGN SHALL BE INSTALLED, AS WELL AS THE STANDARD "PENALTY TOW-AWAY ZONE" SIGN.

FOR SPACES DESIGNATED ON
PLAN AS VAN ACCESSIBLE,
PROVIDE "VAN ACCESSIBLE"
SIGN WITH MINIMUM 2" HIGH
LETTERING MOUNTED
UNDERNEATH RESERVED
PARKING SIGN.

SIGN(S) SHALL BE MOUNTED TO 2" DIAM. FIELD PAINTED STEEL TUBE (UNLESS SPECIFIED TO BE WALL MOUNTED). SET PIPE IN 12" DIAMETER BY 18" DEEP A3 CONCRETE BASE, RECESSED 6" BELOW FINISHED GRADE. COLOR AND PAINT TO BE SELECTED BY OWNER OR ARCHITECT.


SIGN(S) SHALL BE MOUNTED WITH THE BOTTOM OF THE SIGN(S) NO LESS THAN 4' AND NO HIGHER THAN 7' ABOVE ABOVE THE FINISHED GRADE.

THE REQUIRED ITEMS MAY BE CONTAINED ON ONE OR MULTIPLE SIGNS. SUBMIT SHOP DRAWING(S) FOR SIGN

SIGN(S) SHALL COMPLY WITH THE LATEST EDITION OF UFA (UNIFORM FEDERAL ACCESSIBILITY STANDARDS), VUSBC (VIRGINIA UNIFORM STATEWIDE BUILDING CODE), AND THE CODE OF VIRGINIA SECTION 36-99.11.


HANDICAP PARKING SIGN

HS-1



STANDARD CURB & GUTTER


NOT TO SCALE



REVERSE PITCH CURB & GUTTER

NOT TO SCALE

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS. (NOTES)
2. DO NOT SCALE DRAWINGS.
3. DIMENSIONS APPLY FOR ALL RACKS. OPTIONAL HEIGHT OF 42" (1067MM) IS AVAILABLE.
4. THE MODEL NUMBERS INDICATE THE NUMBER OF BIKES EACH BIKE RACK HOLDS.
5. CONTRACTORS NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADDAUSA.com



75 LBS

TOWN ENGINEER	DATE
TOWN PLANNER	DATE

